

# NOIR

## Technical Report

<b>Size:</b>	5.0 – 6.0 m <sup>2</sup>		
<b>Thickness:</b>	1.0 – 1.2 mm		
		<b>Requirements</b>	<b>Our test</b>
<b>Colour fastness to light:</b>	DIN EN ISO 105-B02	≥4	>6
<b>Colour fastness to rubbing*:</b>	DIN EN ISO 11640		
	Dry 500 rubs	≥4	4
	Wet 80 rubs	≥3-4	4-5
	Perspiration 50 rubs	≥3-4	4
<b>Finish adhesion:</b>	EN ISO 11644	≥2N	4N
<b>Tearing load</b>	DIN EN ISO 3377-1	≥20N	41,4N
<b>Flexing endurance:</b>	DIN EN ISO 5402-1	50,000	no damage
<b>Cigarette + match:</b>	BS EN 1021-1 and 2	-	non-ignition
<b>Flammability test:</b>	CA TB 117-2013		non-ignition

### \*Reflecting test results on the leather surface

**Colour fastness to light:** The leather will become lighter as time passes. The light fastness indicates how soon this will appear on the leather. The light fastness is measured on a scale from 1 to 8 (1=lowest and 8=highest)

**Colour fastness to rubbing** is measured on a scale from 1 to 5 (1 = lowest and 5 = highest)

Technical specifications on the shade card are guidelines only. The information may change due to changes in production. Check our website for the most up-to-date technical details at [www.sorensenleather.com](http://www.sorensenleather.com)

**PCP:** According to EU Council Directive 76/769/EEC

**AZO dyes:** According to EU Council Directive 76/769/EEC

**Chrome VI:** Our leather does not contain chrome VI

**REACH:** According to European Community Regulation on chemicals and their safe use (EC 1907/2006)

